

MAVERICK X ds TECHNOLOGIES

INDUSTRY-LEADING PERFORMANCE


We boosted the performance of the proven Rotax® 1000R engine with the industry's first factory-installed turbocharger option enabling it to produce an impressive 121 HP. The Continuously Variable Transmission (CVT) showcases a completely redesigned driven pulley with a NEW Quick Response System (QRS) and an improved drive pulley that allows better power transfer and a faster engagement time.

This NEW package takes all the groundbreaking innovations of the Can-Am Maverick and optimizes them to deliver the most powerful side-by-side vehicle in the industry.



PRECISION-ENGINEERED HANDLING

Every component helps maximize the handling and steering of the Maverick X ds so you maintain full control over its best-in-class power.



Exclusive FOX[†] 2.5 PODIUM[†] RC2 HPG Piggyback shocks with bottom-out control

Front and rear shocks with compression and preload adjustments.



Torsional Trailing A-Arms rear suspension (TTA)

Redesigned with 16 in. of travel.

RIDER-FOCUSED DESIGN

Comfort, convenience and versatility are all packaged ergonomically so both rider and passenger make the most of every ride.



Cockpit


Double A-Arm front

Redesigned with 15 in.

suspension

of travel.

Experience high-end comfort in the Maverick cockpit.







MAVERICK X ds COLOR / ENGINE

Black, White & Manta Green / 1000R

White, Light Grey & Manta Green / 1000R TURBO

Carbon Black & Manta Green / 1000R TURBO



MAVERICK MAX X ds COLOR/ENGINE

Black, White & Manta Green / 1000R

White, Light Grey & Manta Green / 1000R TURBO

Carbon Black & Manta Green / 1000R TURBO

		MAVERICK X ds	MAVERICK MAX X ds	MAVERICK X ds	MAVERICK MAX X ds
ENGINE		1000R		1000R TURBO	
	ТҮРЕ	976 cc, V-twin, liquid cooled, SOHC, 8-valve (4-valves / cyl)		976 cc TURBOCHARGED, V-twin, liquid cooled, SOHC, 8-valve (4-valves / cyl), with integrated intercooler and high-performance Donaldson air filter	
	BORE & STROKE	91 x 75 mm			
	FUEL DELIVERY SYSTEM	iTC™ with EFI and 54 mm Throttle Body, 2 Siemens† VDO injectors			
	STARTING SYSTEM	Electric			
	TRANSMISSION	CVT, sub-transmission Standard en	n with L / H / N / R / P. gine braking	Quick Response System (QRS) CVT, subtransmission with L / H / N / R / P	
	DRIVE TRAIN	Selectable 2WD / 4WD shaft driven with Visco-Lok [‡] QE auto-locking front differential			front differential
UHASSIS	FRAME	Steel			
	CAGE TYPE	2-in. (5.1 cm) diameter, high-strength steel, ROPS-approved			
	STEERING WHEEL ADJUSTMENT	Adjustable tilt steering			
	POWER STEERING	Tri-Mode Dynamic Power Steering (DPS™)			
	FRONT SUSPENSION TYPE	Double A-arm			
	FRONT SHOCKS TYPE	FOX 2.5 PODIUM RC2 HPG Piggyback shocks with dual speed compression, rebound and dual rate spring preload adjustments			
	FRONT SUSPENSION TRAVEL	15 in. (38.1 cm)			
	REAR SUSPENSION TYPE	Torsional Trailing A-arms independent rear suspension (TTA) with sway bar			
	REAR SHOCKS TYPE	FOX 2.5 PODIUM RC2 HPG Piggyback shocks with dual speed compression, rebound, dual rate spring preload adjustments with crossover ring, bottom-out control			
	REAR SUSPENSION TRAVEL	16 in. (40.6 cm)			
	FRONT BRAKES	Dual 220 mm ventilated brakes with hydraulic twin-piston (32 mm) per caliper			
	REAR BRAKES	Dual 214 mm ventilated brakes with hydraulic single-piston (32 mm) per caliper			
	TIRES / FRONT	Maxxis Bighorn 2.0 [†] 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm)			
	TIRES / REAR	Maxxis Bighorn 2.0 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)			
	WHEELS	Aluminum beadlock			
DIMENSIONS	LxWxH	117.3 x 64 x 74.2 in. (297.9 x 162.5 x 188.5 cm)	146.5 x 64 x 78 in. (372.1 x 162.5 x 198 cm)	117.3 x 64 x 74.2 in. (297.9 x 162.5 x 188.5 cm)	146.5 x 64 x 78 in. (372.1 x 162.5 x 198 cm)
	WHEELBASE	88 in. (223.5 cm)	117.5 in. (298.5 cm)	88 in. (223.5 cm)	117.5 in. (298.5 cm)
	GROUND CLEARANCE	13 in. (33 cm)			
	REAR RACK CAPACITY	200 lb (91 kg) with LinQ™	150 lb (68 kg) with LinQ	200 lb (91 kg) with LinQ	150 lb (68 kg) with LinQ
	COCKPIT STORAGE	4.8 gal (18.5 L)	5.2 gal (19.8 L)	4.8 gal (18.5 L)	5.2 gal (19.8 L)
	FUEL CAPACITY	10 gal (37.8 L)			
realunes	INSTRUMENTATION	Multifunction analog / digital gauge			
	ANTI-THEFT SYSTEM	Digitally Encoded Security System (D.E.S.S.™)			
	LIGHTING	240-W from four 60-W projectors with tail lights/ brake lights			
	COLOR(S)	Black, White & Manta Green		White, Light Grey & Manta Green Carbon Black & Manta Green	
	FACTORY WARRANTY	6 months limited warranty			

Some vehicles may be accessorized.









MAVERICK X ds GEAR AND ACCESSORIES

Can-Am Maverick X ds accessories make the ultimate ride even better. Like hard- and soft-top roofs for protection against the elements, lightweight aluminum doors and intense LED light bars. Designed and tested by the same people who created your Maverick X ds, all accessories will fit perfectly and be eligible for coverage under our warranty.

To build your own or explore the full lineup of gear and accessories, visit Can-AmOffroad.com

©2014 Bombardier Recreational Products Inc (BRP). All rights reserved. , and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. ‡Visco-Lok is a trademark of GKN Viscodrive GmbH. †All other trademarks are the property of their respective owners. *Certain conditions may apply. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Drive responsibly. Printed in Canada. PN: 716001247.